



2012 Jeep® Grand Cherokee SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions are measured at curb weight with standard tires and wheels.

Note: Information shown is correct at time of publication, and is subject to change without notice.

GENERAL INFORMATION

Body Style	Four-door sport-utility vehicle
Construction	Steel uniframe
Assembly Plant	Jefferson Avenue North Assembly Plant, Detroit, Mich.
EPA Vehicle Class	Multi-purpose vehicle
Introduction	Spring 1992 as a 1993 model

ENGINE: 3.6-LITER DOHC V-6

Availability	Standard on all models (2WD and 4WD)
Type and Description	60-degree V-type, liquid-cooled
Displacement	220 cu. in. (3604 cu. cm) 3.78 x 3.27 (96.0 x 83.0)
Bore x Stroke	3.77 x 3.26 (96 x 83)
Valve System	Chain-driven DOHC, 24 valves and hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Aluminum deep-skirt block, aluminum alloy heads
Compression Ratio	10.2:1
Power (est.) (SAE J2723)	290 hp (209 kW) at 6,400 rpm
Torque (est.) (SAE J2723)	260 lb.-ft. (353 N•m) at 4,800 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R + M)/2
Oil Capacity	6.0 qt. (5.7L)
Coolant Capacity	14.0 qt. (13.25L)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors and internal engine features ^(a)
EPA Fuel Economy mpg (City/Hwy)	17/23 — 2WD 16/23 — 4WD
Assembly Plant	Trenton South Engine Plant, Trenton, Mich.

(a) Meets Calif. LEV II+ evaporative emission requirements in CA, NY, MA, ME, VT. Meets Tier 2, meets Federal Bin 4+ emission requirements and Clean Fuel Fleet Certification (CCF-LEV) in all other 45 states.

**ENGINE: 5.7-LITER MDS V-8**

Availability	Optional on all models
Type and Description	90-degree V-type, liquid-cooled
Displacement	345 cu. in. (5654 cu. cm)
Bore x Stroke	3.92 x 3.58 (99.5 x 90.9)
Valve System	Variable-valve timing, pushrod-operated overhead valves, 16 valves, eight deactivating and eight conventional hydraulic lifters, all with roller followers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
Power (est.) (SAE J2723)	360 hp (268 kW) at 5,150 rpm
Torque (est.) (SAE J2723)	390 lb.-ft. (520 N•m) at 4,250 rpm
Max. Engine Speed	5,800 rpm (electronically-limited)
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — recommended; unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	7 qt. (6.6L)
Coolant Capacity	14.5 qt. (13.72L)
Emission Controls	Dual close-coupled three-way catalytic converters, quad heated oxygen sensors and internal engine features ^(a)
EPA Fuel Economy mpg (City/Hwy)	14/20 — 2WD 13/20 — 4WD
Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico

(a) Meets Calif. LEV II+ evaporative emission requirements in CA, NY, MA, ME, VT and Federal Bin 5+ Tier II emissions and Clean Fuel Fleet Certification (CCF).

TRANSMISSION: W5A580 AUTOMATIC, FIVE-SPEED OVERDRIVE

Availability	Included with 3.6-liter V-6 engine
Description	Electronic Range Select (ERS) driver-interactive manual control and electronically-modulated torque converter clutch
Gear Ratios	
1 st	3.59
2 nd	2.19
3 rd	1.41
4 th	1
5 th	0.83
Reverse	3.16
Final Drive Ratio	3.06:1
Overall Top Gear	2.54

**TRANSMISSION: 65RFE AUTOMATIC, SIX-SPEED**

Availability	Included with 5.7-liter engine
Description	Three planetary gear sets, one overrunning clutch, with Electronic Range Select (ERS) driver interactive control, electronically controlled torque converter clutch
Gear Ratios	
1 st	3
2 nd	1.67
3 rd	1.50
4 th	1
5 th	.75
6 th	.67
Reverse	3
Final Drive Ratio	3.47
Overall Top Gear	2.32

TRANSFER CASE: MP 3010

Availability	Optional with 3.6-liter engine
Type	Single-speed
Operating Mode	Full-time AWD
Low Range Ratio	None
Torque Split, Front/Rear	50/50

TRANSFER CASE: MP 3022

Availability	Optional with the 3.6-liter and 5.7-liter engine
Type	Two-speed, electronically shifted
Operating Modes	4x4 Low (Lock), Neutral; full-time active 4x4
Low Range Ratio	2.72
Torque Split, Front/Rear	Variable

FRONT AXLES

Differential Type	Conventional
Availability	Standard on 4x4 models with 3.6-liter and 5.7-liter engines
Ring Gear Diameter	7.7 in. (195 mm)
Axle Ratios	3.07:1 — 3.6-liter engine; 3.45:1 — 5.7-liter engine

REAR AXLES

Differential Type	Conventional
Availability	Standard on all engines
Ring Gear Diameter	8.4 in. (215 mm) — 3.6-liter engine, 8.9 in. (225 mm) — 5.7 liter engine
Axle Ratios	3.06:1 — 3.6-liter engine; 3.47:1 — 5.7-liter engine
Differential Type	Electronic Limited Slip Differential (ELSD)



+ GRAND CHEROKEE

SPECIFICATIONS

Availability	Optional on 4x4 V-8 models with MP 3022 transfer case
Ring Gear Diameter	Same as conventional
Axle Ratios	3.45 — 5.7-liter engine

ELECTRICAL SYSTEM

Alternator	160-amp; 180-amp or 220-amp depending on option content
Battery	Group 65 maintenance-free 750CCA

DIMENSIONS AND CAPACITIES

Wheelbase	114.8 (2915)
Track, Front	63.9 (1623)
Track, Rear	64.1 (1627)
Overall Length	189.8 (4822)
Overall Width (Width at Mirrors)	84.8 (2154)
Body Width	76.5 (1943)
Overall Height (at Roof Rail / at Antenna)	69.3 (1761) / 70.0 (1779)
Load Floor Height (Std Susp. / Air Susp.)	32.4 (822) / 31.8 (807)
Sill Step Height (Std Susp. / Air Susp.)	20.5 (520) / 20.0 (508)
Ground Clearance (with P245/70R17 Tire and 3.6L Engine) (Std Susp. / Air Susp. – Pos#2)	8.6 (218) / 10.6 (270)
Chassis (Fuel Tank) (Std Susp. / Air Susp. – Pos#2)	9.6 (243) / 11.6 (294)
Front Axle (Std Susp. / Air Susp. – Pos#2)	9.3 (236) / 10.6 (269.5)
Rear Axle (Std Susp. / Air Susp. – Pos#2)	10.0 (253) / 12.0 (303.5)
Approach Angle, Degrees (Std Susp. / Air Susp. – Pos#2, air-dam off)	26.3 / 34.3
Ramp Breakover Angle, Degrees (Std Susp. / Air Susp. – Pos#2)	18.8 / 23.1
Departure Angle, Degrees (Std Susp. / Air Susp. – Pos#2)	26.5 / 29.3
Frontal Area	31.0 sq. ft. (2.88 sq. m)
Drag Coefficient	Approximately 0.37
Aero CdA	11.6 (Cd x cross-sectional area)
Fuel Tank Capacity	24.6 gal. (93.1L)



+ GRAND CHEROKEE

SPECIFICATIONS

ACCOMMODATIONS

Seating Capacity, Front/Second	2/3
Front Seat	
Head Room	39.9 (1013)
Legroom	40.3 (1025)
Shoulder Room	58.7 (1491)
Hip Room	57.0 (1449)
Seat Travel	11.0 (280)
SAE Volume	54.6 cu. ft. (1.55 cu. m)
Rear Seat	
Head Room	39.2 (995)
Legroom	38.6 (981)
Shoulder Room	58.0 (1474)
Hip Room	56.2 (1428)
Knee Clearance	4.3 (110)
Couple	34.6 (880)
SAE Volume	50.8 cu. ft. (1.4 cu. m)
Cargo Volume	
Behind Rear Seat	35.1 cu. ft. (0.99 cu. m)
Rear Seats Folded	68.7 cu. ft. (1.95 cu. m)

WEIGHTS (Estimates)

	MODEL	ENGINE	GVWR ^(a) lbs. (kg)	CURB WEIGHT ^(b) lbs. (kg)	PAYLOAD ^(c) lbs. (kg)
2WD	Laredo	3.6-liter	6500 (2948)	4470 (2028)	2030 (920)
		5.7-liter	6500 (2948)	4780 (2169)	1720 (780)
	Limited	3.6-liter	6500 (2948)	4600 (2087)	1900 (860)
		5.7-liter	6500 (2948)	4920 (2232)	1580 (715)
	Overland	5.7-liter	6500 (2948)	4920 (2232)	1580 (715)
	Overland Summit	5.7-liter	6500 (2948)	4920 (2232)	1580 (715)
4WD	Laredo	3.6-liter	6500 (2948)	4660 (2114)	1840 (835)
		5.7-liter	6500 (2948)	5020 (2278)	1480 (670)
	Limited	3.6-liter	6500 (2948)	4850 (2201)	1650 (750)
		5.7-liter	6800 (3084)	5150 (2336)	1660 (750)
	Overland	5.7-liter	6800 (3084)	5210 (2364)	1590 (720)
	Overland Summit	5.7-liter	6800 (3084)	5210 (2364)	1590 (720)

(a) Gross Vehicle Weight Rating.

(b) Curb weight includes standard equipment and full quantities of fuel, lubricant and coolant.

(c) Payload is the maximum allowable weight of driver, passengers, cargo, and options, rounded to the nearest 10 lbs. (5kg).



WEIGHT DISTRIBUTION, F/R

	MODEL	ENGINE	DISTRIBUTION
2WD	Laredo	3.6-liter	51/49
		5.7-liter	54/46
	Limited	3.6-liter	51/49
		5.7-liter	53/47
	Overland	5.7-liter	54/46
4WD	Laredo	3.6-liter	53/47
		5.7-liter	55/45
	Limited	3.6-liter	52/48
		5.7-liter	54/46
	Overland	5.7-liter	54/46
Overland Summit	5.7-liter	54/46	

BODY

4x2

Layout	Longitudinal front engine, rear drive
Construction	Steel uniframe

4x4

Layout	Longitudinal front engine, transfer case with full-time four-wheel drive
Construction	Steel uniframe

SUSPENSION

Front	Short- and long-arm independent (SLA), coil springs, gas-charged, twin-tube coil-over shock absorbers, upper- and lower-control arms ("A" arms), stabilizer bar
Rear	Multi-link rear suspension, coil spring, twin tube shocks (including load leveling for towing), aluminum lower control arm, independent upper links (tension and camber) plus a separate toe link.

STEERING

Type	Power rack and pinion (V-8) Electro-hydraulic Power Steering (V-6)
Steering Ratio	18.9:1 — on center; 15.7:1 — at full lock
Turn Circle	37.1 ft. (11.3 m)
Lock-to-Lock Steering Wheel Rotations	3.67



BRAKES

Front

Size and Type	12.9 x 1.2 (328 x 30) vented disc with 1.89 (48) two-piston pin-slider caliper and ABS
Swept Area	282 sq. in. (1820 sq. cm)
Rear	
Size and Type	12.6 x 0.55 (320 x 14) disc with 1.89 (48) single-piston pin-slider caliper and single-channel ABS ^(b)
Swept Area	257 sq. in. (1658 sq. cm)
Power Assist	Single-rate, tandem diaphragm vacuum

(a) Turning diameter is measured at the outside of the tires at curb height. Turning diameters and steering wheel turns, lock-to-lock, may differ with optional tires and wheels.

(b) Three-channel ABS standard on 4x2. Four-channel ABS standard on 4x4.

TIRES

Standard — Laredo

Size and Type	P245/70R17
Mfr. and Model	Goodyear Fortera HL Black Sidewall All-Season — OWL Optional
Revs per Mile	685

Standard — Limited; Optional Laredo

Size and Type	P265/60R18
Mfr. and Model	Michelin Latitude Tour Black Sidewall All-Season
Revs per Mile	691

Standard — Overland; Optional Limited

Size and Type	P265/50R20
Mfr. and Model	Goodyear Fortera HL Black Sidewall All-Season
Revs per Mile	690

Optional — Laredo, Limited and Overland

Size and Type	P265/60R18
Mfr. and Model	Michelin Latitude Tour OWL All-Season
Revs per Mile	691

Standard — Overland Summit

Size and Type	P265/50R20
Mfr. and Model	Goodyear Fortera HL Black Sidewall All-Season
Revs per Mile	690



+ GRAND CHEROKEE

SPECIFICATIONS

WHEELS

Type and Material	Cast-aluminum
Sizes	17 in. x 8.0 in. aluminum painted wheels 18 in. x 8.0 in. aluminum polished wheels 20 in. x 8.0 in aluminum premium with painted pockets

TRAILER TOWING^(a)

	ENGINE	AXLE RATIO	MAXIMUM TRAILER WEIGHT ^(b) LBS. (KG)
2WD	3.6-liter V-6	3.06	5000 (2269)
	5.7-liter V-8	3.47	7400 (3400)
4WD	3.6-liter V-6	3.06	5000 (2269)
	5.7-liter V-8	3.47	7200 (3300)

(a) All models can tow trailers up to 5,000 pounds with the addition of a trailer hitch. For towing heavier trailers up to the Maximum Trailer Weight Ratings shown in the Trailer Towing chart, the vehicle must be equipped with the Trailer Tow Group Class IV for the 5.7-liter engines for North America.

(b) Maximum Trailer Weight = GCWR - Curb Wt. with hitch - 300 lbs. (allowance for driver and passenger) and must be decreased by the weight of optional equipment, cargo and additional passengers. Maximum trailer weights shown are rounded to the nearest 50 lbs. Tongue weight should be 10-15% of loaded trailer weight but may not cause vehicle to exceed GVWR or GAWR. Load equalizing hitch recommended for trailers over 2,000 pounds.

+ + +



+ GRAND CHEROKEE

FEATURE AVAILABILITY

2012 Jeep® Grand Cherokee FEATURE AVAILABILITY

LEGEND: S = Standard, O = Optional, P = Package, — = Not available
 Complete package information is listed at the end of the Feature Availability section.
 NOTE: Information shown is correct at time of publication and is subject to change.

	Laredo	Limited	Overland	Overland Summit
EXTERIOR				
Body				
Body-color fascias with bright insert	—	S	S	S
Body-color door handles	S	—	—	—
Bright door handles	—	S	S	S
Bright daylight opening (DLO), bright grille	S	S	S	S
Bright exhaust tip	—	S	S	S
Bright license plate brow	S	S	S	S
Chrome bodyside molding and bright side roof rails (Bright side roof rail not standard, but packaged (P) on Laredo)	S	S	S	S
Deep tint sunscreen glass	S	S	S	S
Door sill scuff pads	S	—	—	—
Door sill scuff pads with Jeep® logo (bright insert)	—	S	S	S
Dual-pane panoramic sunroof w/power shade	—	S	S	S
Flipper liftgate glass	S	S	S	S
Grille (black slot insert)	S	S	—	—
Grille (back mesh insert)	—	—	S	—
Grille (chrome mesh insert)	—	—	—	S
Power liftgate	—	P	S	S
Sunroof, power front (with rear DVD)	—	P	P	S
Colors				
Bright Silver Metallic Clear Coat, Brilliant Black Crystal Clear Coat, Stone White Clear Coat, Mineral Gray Metallic Clear Coat, Deep Cherry Red Pearl Coat, True Blue Pearl Coat, Maximum Steel Clear Coat, Winter Chill Pearl Coat (late availability), Black Forest Green Pearl Coat	O	O	O	—
Summit color availability - Mineral Gray Pearl Coat, Rugged Brown Metallic, Winter Chill Pearl Coat (late availability), and Brilliant Black Crystal	—	—	—	O
Lights				
Automatic halogen headlamps and fog lamps	S	S	S	S
Auto headlamp leveling system	—	S	S	S
Bi-xenon headlamps	—	S	S	S
Daytime running lamps	—	S	S	S
SmartBeam® headlamps	—	S	S	S



+ GRAND CHEROKEE

FEATURE AVAILABILITY

	Laredo	Limited	Overland	Overland Summit
Mirrors				
Chrome power heated memory multi-functioning mirrors, fold away	—	S	S	S
Body-color power, heated folding mirrors, fold away	S	—	—	—
Wipers				
Rain-sensitive windshield	—	S	S	S
Rear window wiper/washer and rear window defroster	S	S	S	S
INTERIOR				
Auxiliary power				
12-volt auxiliary power outlets — front and rear	S	S	S	S
115-volt auxiliary power outlet	P	S	S	S
Air Conditioning				
Air conditioning with automatic dual zone temperature control	—	S	S	S
Air conditioning with manual dual zone temperature control	S	—	—	—
Air filtering	S	S	S	S
Illuminated cup holders	S	S	S	S
Interior colors				
Black	O	O	O	—
Dark Graystone/Medium Graystone	O	—	—	—
Black/Light Frost Beige	—	O	—	—
Dark Frost Beige/Light Frost Beige	—	—	O	—
New Saddle / Black	—	—	O	S
Instrument cluster with tachometer and dual note electric horns	S	S	S	S
Laminated front door glass	S	S	S	S
Leather-wrapped shift knob	—	S	S	S
Luxury door trim panel	—	—	S	S
Front/rear floor mats	S	S	S	S
Passenger assist handles	S	S	S	S
Premium door trim panel	—	S	—	—
Premium silver strakes in rear cargo area	—	S	S	S
Premium insulation group	S	S	S	S
Radio/driver seat/mirrors memory	—	S	S	S
Real wood bezels	—	—	S	S



+ GRAND CHEROKEE

FEATURE AVAILABILITY

	Laredo	Limited	Overland	Overland Summit
Seats				
Cloth low-back bucket seats	S	—	—	—
Front passenger seat forward fold flat	S	—	—	—
Heated front seats	—	S	S	S
Heated second-row seats	—	S	S	S
Power eight-way driver seat and power four-way driver lumbar	P	S	S	S
Power eight-way driver/passenger seats	—	S	S	S
Power driver/pass four-way lumbar	—	S	S	S
Leather-trimmed bucket seats	—	S	—	—
Premium leather-trimmed bucket seats with piping	—	—	S	S
Ventilated front seats	—	P	S	S
Overland, Summit embroidery with unique stitching	—	—	—	S
Sound systems and entertainment				
Six speakers	S	—	—	—
Nine amplified speakers with subwoofer and 506 watt amp	—	S	S	S
SIRIUS Travel Link	—	S	S	S
SIRIUS Satellite Radio	P	S	S	S
AM/FM/CD/MP3 radio	S	—	—	—
AM/FM/CD/DVD/HDD/MP3 radio with Garmin navigation (late availability)	—	S	—	—
CD/DVD/HDD radio with premium navigation including voice recognition, dead reckoning and SIRIUS Real Time Traffic	—	O	S	S
Steering column				
Power tilt/telescope steering wheel	—	P	S	S
Tilt/telescope steering column	S	S	—	—
Steering wheel				
Speed control	S	S	S	S
Leather-wrapped heated steering wheel	—	P	—	—
Wood/leather-wrapped heated steering wheel with memory and audio controls	—	—	S	S
Leather-wrapped steering wheel with audio controls	S	S	—	—
Storage				
Center floor console and overhead console	S	S	S	S
Cargo compartment cover	P	S	S	S
Cargo net	—	—	S	S
Cargo trim panel with cargo tie-down loops	S	S	S	S
Cargo trim panel with storage	S	—	—	—
Sun visors with illuminated vanity	S	S	S	S
Electronic Vehicle Information Center (EVIC)	S	S	S	S



+ GRAND CHEROKEE

FEATURE AVAILABILITY

	Laredo	Limited	Overland	Overland Summit
POWERTRAIN AND CHASSIS				
Alternator				
160-amp alternator	S	—	—	—
180-amp alternator	—	S	S	S
220-amp alternator	—	P	P	S
Axle ratio				
215 mm rear axle, 3.06 axle ratio	S	S	S	S
225 mm rear axle, 3.47 axle ratio	—	P	P	P
230 mm rear axle, 3.45 axle ratio	—	P	P	P
Brakes				
Anti-lock four-wheel disc brakes, hydraulic assist brake	S	S	S	S
Anti-lock four-wheel disc brakes (4x4 V-8 only)	—	S	S	S
Engines				
3.6-liter V-6 engine with variable valve timing (VVT), five-speed transmission	S	S	S	S
5.7-liter multi-displacement system (MDS) V-8 with VVT, six-speed transmission	—	O	O	O
Engine oil cooler	S	S	S	S
Fuel tank				
24.6 gallon fuel tank	S	S	S	S
Quadra-Drive II® 4WD system (4x4 V-8 only)	—	P	S	S
Quadra-Lift™ air suspension system (4x4 only)	—	P	S	S
Power rack-and-pinion steering and power steering cooler (V-8) Electro-hydraulic Power Steering (V-6)	S	S	S	S
Selec-Terrain™ traction control system (4x4 only)	P	S	S	S
Transfer case				
Single-speed transfer case (4x4 V-6 only)	S	—	—	—
Two-speed on-demand transfer case (4x4 only)	P	S	S	S
Tires				
P245/70R17 BSW on/off road tires	S	—	—	—
P245/70R17 OWL on/off road tires	P	—	—	—
P265/60R18 BSW on/off road tires	—	S	—	—
P265/60R18 OWL on/off road tires	—	P	P	P
265/50R20 BSW all-season tires	—	O	S	S
Compact full-diameter spare tire	S	S	S	S
Full-size spare tire	P	P	P	P
Chrome tow hooks	—	—	—	S



+ GRAND CHEROKEE


FEATURE AVAILABILITY

	Laredo	Limited	Overland	Overland Summit
Wheels				
17 in. x 8.0 in. aluminum painted wheels	S	—	—	—
18 in. x 8.0 in. aluminum polished wheels	—	S	P	P
20 in. x 8.0 in aluminum premium painted wheels	—	O	S	S
20 in. x 8.0 in aluminum premium with painted pockets	—	—	—	S
Compact spare wheel	S	S	S	S
Full-size steel spare wheel	P	P	P	P
SAFETY AND SECURITY				
Active head restraints	S	S	S	S
Child seat anchor system with child seat upper tether anchor	S	S	S	S
Electronic stability control (ESC) with brake assist	S	S	S	S
Enhanced accident response	S	S	S	S
Illuminated entry, glove box lamp and LED lighting	S	S	S	S
Hill-decent Control (HDC)	P	P	P	P
Hill-start Assist (HAS)	S	S	S	S
Interior removable/rechargeable light	S	S	S	S
Keyless Enter-N-Go with Sentry Key® theft deterrent	P	S	S	S
Locking glove box	S	S	S	S
ParkView® rear back-up camera	—	S	S	S
Parksense® rear park assist system	—	S	S	S
Power accessory delay	S	S	S	S
Power front windows with one-touch up/down and power locks	S	S	S	S
Power locking fuel filler	S	S	S	S
Remote start system	P	S	S	S
Security alarm	P	S	S	S
Supplemental side curtain front/rear air bags	S	S	S	S
Supplemental front seat side air bag	S	S	S	S
Tire-pressure monitoring (TPM) warning lamp	S	—	—	—
Tire-pressure monitoring (TPM) display	—	S	S	S
Uconnect® Phone handsfree communication	O	S	S	S
Universal garage door opener	P	S	S	S



+ GRAND CHEROKEE

FEATURE AVAILABILITY

	Laredo	Limited	Overland	Overland Summit
PACKAGES / EQUIPMENT GROUPS				
Laredo E Group — Includes Keyless Enter-N-Go with Sentry Key® theft deterrent, Power eight-way driver seat and power four-way driver lumbar, SIRIUS Satellite Radio, bright side roof rails	O	—	—	—
All-weather package — Includes Select Terrain, two-speed transfer case with low-range, engine block heater, daytime running lamps, remote start, tow hooks and Mopar slush mats and cargo liner	O	—	—	—
Rear DVD Entertainment Center — Includes rear-seat video system, rear overhead console, power sunroof	—	O	O	O
Luxury Group II — Includes power liftgate, heated steering wheel, power tilt/telescope steering column and ventilated front seats	—	O	—	—
Off Road Adventure I — Includes skid plate group, two-speed on-demand transfer case, Selec-Terrain™ system, Trail Rated® badge, full-size spare tire, steel spare wheel, P245/70R17 OWL on/off road tires (Laredo only), P265/60R18 OWL on/off road tires	O	O	—	—
Off Road Adventure II — Includes Quadra-Drive® 4WD system (V-8 only), two-speed on-demand transfer case, Selec-Terrain, Quadra-Lift air suspension system, Trail Rated badge, full-size spare tire, steel spare wheel, P265/60R18 OWL on/off-road tires, skid plate group	—	O	O 	
Security and Convenience Group — Includes Uconnect® Phone handsfree communication, universal consumer interface, rearview auto-dim mirror with microphone, remote start, security alarm, 115-volt auxiliary power outlet, universal garage door opener and cargo compartment cover	O	—	—	—
Advanced Warning System and Adaptive Cruise Control (ACC) (must have Luxury Group II Limited only) — Includes adaptive speed control, Forward Collision Warning (FCW), Blind-spot Monitoring (BSM) and Rear Cross Path (RCP) detection (late availability)	—	O	O	S
Trailer Tow Group (V-6 only) — Includes rear load-leveling suspension (not available with 4x2 or Quadra-Lift air suspension system), full-size spare tire, steel spare wheel, Class IV receiver hitch with seven- and four-pin wiring harness	O	O	S	S
Trailer Tow Group IV (V-8 only) — Includes heavy-duty engine cooling, engine oil cooler, 220-amp alternator, rear load-leveling suspension (not available with Quadra-Lift air suspension system), full-size spare tire, steel spare wheel, Class IV receiver hitch with seven- and four-pin wiring harness	—	O	P	P

+ + +